

Copyright

The interpretation right of this product specification belongs to BOE MLED. Without the signed permission of BOE MLED, any other individual or organization is not allowed, in any form, to excerpt, reproduce, copy, translate, edit or publish this product specification. This product specification is subject to modification without prior notice.



SPEC. NUMBER

-

Product Group

MLED

REV.

-

Release Date

2024.04.07

Page

1

Product Pre-Spec

BYB025

Rev. 1

BOE MLED Technology Co., Ltd.

Copyright

The interpretation right of this product specification belongs to BOE MLED. Without the signed permission of BOE MLED, any other individual or organization is not allowed, in any form, to excerpt, reproduce, copy, translate, edit or publish this product specification. This product specification is subject to modification without prior notice.



SPEC. NUMBER

-

Product Group

MLED

REV.

-

Release Date

2024.04.07

Page

2

1. Product Features

- 1) The panel is silver in color, fashionable and beautiful, with good texture, a sense of luxury, and strong lines.
- 2) Aluminum body, efficient heat dissipation, stable running.
- 3) Lightweight design, $\leq 25\text{KG/m}^2$, easy to handle, low transportation and installation costs, saving steel structures.
- 4) Good protective performance. The protection level is IP65, which can prevent rainstorm, typhoon and salt fog.
- 5) No need for air conditioning, saving equipment costs and electricity bills.
- 6) It can be installed without any other protection, beautiful and convenient.
- 7) Multiple panel sizes available, including 640x640、480x640、960x640, and more.
- 8) It can achieve various irregular shapes such as curve screen、glasses-free 3D and seamless right angle splicing.

2. Product Image



SPEC. NUMBER
-

Product Group
MLED

REV.
-

Release Date
2024.04.07

Page
3

3. Main Technical Parameters

Parameter		Value
Physical Parameters	LED Type	SMD1415
	Pixel Pitch (mm)	2.5
	Panel Dimensions (WxHxD)/(mm)	640×640×75
	Pixel Per Panel	256×256
	Weight (kg/m²)	25
	Panel Material	Aluminum
	Module Dimensions (WxH)/(mm)	160×640
Photoelectric Parameters	Brightness (nit)	4500
	Refresh Rate (Hz)	≥3840
	Gray scale (bit)	14
	Contrast Ratio	4000:1
	Color Temperature (K)	2000~9500
	Viewing Angle (H/V) (°)	160/140
	AC Operating Voltage (V)	220~240V @ 50/60Hz
	Power Consumption (Max./Avg.)(W/m²)	750/250
Application Parameters	Storage Temperature (°C)	- 40~ + 60
	Operating Temperature (°C)	- 20~ + 50
	Storage Humidity (RH)	10 % ~80 % (No Condensation)
	Operating Humidity (RH)	10 % ~90 % (No Condensation)
	IP Rating (Front/Rear)	IP65/IP65
	LED Lifetime (H)	100000
	Module Maintenance	Rear
	PSU & Others Maintenance	Rear
	Panel Installation Type	Fixed
	Certificates	/

Remark:

- 1、Power consumption and brightness tolerance: 315%, according to the actual situation.
- 2、Parameters may be updated