

Copyright

The interpretation right of this product specification belongs to BOE MLED. Without the signed permission of BOE MLED, any other individual or organization is not allowed, in any form, to excerpt, reproduce, copy, translate, edit or publish this product specification. This product specification is subject to modification without prior notice.



SPEC. NUMBER

-

Product Group

MLED

REV.

-

Release Date

2024.04.07

Page

1

Product Pre-Spec

BYB080Pro

Rev. 1

BOE MLED Technology Co., Ltd.

SPEC. NUMBER  
-

Product Group  
MLED

REV.  
-

Release Date  
2024.04.07

Page  
2

1. Product Features

- 1) The panel is silver in color, fashionable and beautiful, with good texture, a sense of luxury, and strong lines.
- 2) Aluminum body, efficient heat dissipation, stable running.
- 3) Lightweight design,  $\leq 25\text{KG/m}^2$ , easy to handle, low transportation and installation costs, saving steel structures.
- 4) Good protective performance. The protection level is IP66, which can prevent rainstorm, typhoon and salt fog.
- 5) Dual voltage drive, a new benchmark for outdoor energy-saving, saving more than 30% energy compared to traditional products.
- 6) No need for air conditioning, saving equipment costs and electricity bills.
- 7) It can be installed without any other protection, beautiful and convenient.
- 8) Between panels are connected by professional connectors, flexible and convenient installation and maintenance, front and rear installation and maintenance.
- 9) Multiple panel sizes available, including 960x960、480x960、960x640、480x640, and more.
- 10) It can achieve various irregular shapes such as curve screen、glasses-free 3D and seamless right angle splicing.

2. Product Image



Copyright

The interpretation right of this product specification belongs to BOE MLED. Without the signed permission of BOE MLED, any other individual or organization is not allowed, in any form, to excerpt, reproduce, copy, translate, edit or publish this product specification. This product specification is subject to modification without prior notice.



SPEC. NUMBER  
-

Product Group  
MLED

REV.  
-

Release Date  
2024.04.07

Page  
3

3. Main Technical Parameters

Parameter		Value
Physical Parameters	LED Type	SMD2727
	Pixel Pitch (mm)	8
	Panel Dimensions (WxHxD)/(mm)	960×960×75
	Pixel Per Panel	120×120
	Weight (kg/m²)	25
	Panel Material	Aluminum
	Module Dimensions (WxH)/(mm)	160×960
Photoelectric Parameters	Brightness (nit)	10000
	Refresh Rate (Hz)	≥3840
	Gray scale (bit)	16
	Contrast Ratio	19000:1
	Color Temperature (K)	2000~9500
	Viewing Angle (H/V) (°)	160/140
	AC Operating Voltage (V)	220~240V @ 50/60Hz
	Power Consumption (Max./Avg.)(W/m²)	550/180
Application Parameters	Storage Temperature (°C)	- 40~ + 60
	Operating Temperature (°C)	- 20~ + 60(-40°C Optional)

Copyright

The interpretation right of this product specification belongs to BOE MLED. Without the signed permission of BOE MLED, any other individual or organization is not allowed, in any form, to excerpt, reproduce, copy, translate, edit or publish this product specification. This product specification is subject to modification without prior notice.



SPEC. NUMBER  
-

Product Group  
MLED

REV.  
-

Release Date  
2024.04.07

Page  
4

	Storage Humidity (RH)	10 % ~80 % (No Condensation)
	Operating Humidity (RH)	10 % ~90 % (No Condensation)
	IP Rating (Front/Rear)	IP66/IP66
	LED Lifetime (H)	100000
	Module Maintenance	Front/Rear
	PSU & Others Maintenance	Front/Rear
	Panel Installation Type	Fixed
	Certificates	CB/CE/ETL/FCC/ROHS2.0/CCC

Remark:

- 1、Power consumption and brightness tolerance:  $\pm 15\%$ , according to the actual situation.
- 2、Parameters may be updated.

4. Plane Structure of the Product

